

**DESCRIPTION**

PR-N3284 is a co-extruded, polyethylene film (2 mils, 8.5 ounce) that offers temporary protection of metals, building panels, appliances, electronics, automotive parts, and more. The protective film will help prevent scratches, scuff marks, and dirt from damaging surfaces or marring your finished products. The protective film is coated with a special acrylic adhesive. Available in transparent, this protective film adheres to surfaces when you apply light pressure—no need for heat, water, or an additional adhesive.

**APPLICATIONS**

- Metals
- Building panels
- Appliances (including refrigerator insulation panels)
- Electronics
- Automotive parts
- Garage door panels
- Metal roofing
- Basement windows
- Painted PVC

**FEATURES & BENEFITS**

- Co-extruded film engineered with a special acrylic adhesive
- Self-adhesive
- Pressure-sensitive

**PRODUCT CONSTRUCTION**

<b>Backing</b>	Co-Extruded Polyethylene film
<b>Adhesive</b>	Acrylic

**TECHNICAL DATA**

<b>Thickness</b>	2.5 mils
<b>Tensile</b>	6 lbs/in
<b>Adhesion</b>	4 oz/in
<b>Maximum Temperature Resistance</b>	60°C (140°F)
<b>Elongation</b>	Long. >300% / Trans. >500%
<b>Color</b>	Black/White, Blue, Transparent, White
<b>Sizes</b>	Please call for sizes and availability

**STORAGE & USAGE CONDITIONS:** Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application, and the user must, by test or otherwise, determine suitability for purpose; ECHOTape makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for ECHOTape to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.